


TECHNICAL STUDY




**Flame
retardant**



**Improved
dispersion**



**Reduced
costs**



**Improved mechanical
properties**



**EFFECTS OF CEVO® 3105 IN HALOGEN FREE
FLAME-RETARDENT GLASS FIBRE REINFORCED PA**

**Achievement of the UL 94 V0 Standard and
improved mechanical properties**

Introduction

The following problems frequently occur in the manufacture of glass fibre reinforced, flame retardant polyamide formulations using halogen-free flame retardants:

- Foaming of the compound at the extruder head due to the shear sensitivity of the flame retardant and the associated release of hypophosphorous acid.
- As a result: partial chain degradation of the polyamide into the oligomeric range.
- Achieving an inadequate level of mechanical properties and fluctuating burning behaviour due to insufficient homogeneous distribution of the high quantities of glass fibres and flame retardant.

A well-balanced input of shear energy is indispensable in order to achieve an optimum glass fibre length distribution and a homogeneous distribution of both, glass fibres and flame retardant. CEVO® 3105 regulates the shear stress, triggered by the high concentrations, and thus protects the sensitive flame retardant from undesired decomposition during incorporation.

Moreover the distribution of the fillers has a positive effect on the mechanical properties of the final parts. The also improved distribution of the flame retardant improves its effectivity.

Results

Tab. 1: Formulations and properties

Formulation	PA6/66 [%]	Glas fibre [%]	Glas beads [%]	Exolit OP 1311 [%]	Stabiliser ¹⁾ [%]	CEVO® 3105 [%]
1	60,4	20,0	-	18,0	0,4	1,0
2	58,4	25,0	-	15,0	0,4	1,0
3	53,4	25,0	5,0	15,0	0,4	1,0

¹⁾ Combination of phenolic/phosphitic antioxidants. Alternative: copper stabilisation (100 - 150 ppm Cu); applicable mainly for black compounds.

Tab.2: Mechanical properties and flame retardancy

Formulation	MVR275 ^{°C/5kg} [cm ³ /10 min]	Tensile strength [Mpa]	Elongation at break [%]	Tensile modulus [Mpa]	Impact strength [kJ/m ²]	Notched impact strength [kJ/m ²]	UL 94 [1,6mm]	CTI [V]	GWT [° C]
1	29	115	2,9	8120	63	9,5	V0	-	-
2	29	130	2,9	9245	77	12,0	V0	-	-
3	70	130	2,9	9600	68	10,0	V0	600	960

The design of the formulations 1. – 3. enables the flame retardant to be incorporated effectively – yet gently – even at a total of 30% filler amount (-> formulation 3.).

The formulations meet the requirement for a V0 classification in accordance with UL 94 and achieve a high level of mechanical properties, comparable to PA6 GF30 or PA66 GF30.

Further requirements of the electrical industry were also achieved: CTI 600 V (Comparative tracking indices of solid insulating materials; IEC 60112:2020) and Glow wire resistance 960 °C (IEC 60695-2-1).

The proportion of CEVO® 3105 can be reduced experimentally in small steps under certain circumstances, depending on the screw geometry and the frictional energy occurring in each case.

Conclusion

In the present study, it has been demonstrated, that CEVO® 3105 regulates the shear stress in PA with high filler loads and thus protects the sensitive flame retardant from undesired decomposition during incorporation. Moreover the distribution of fillers has a positive effect on the mechani-

cal properties of the final parts. The improved distribution of the flame retardant improves its effectiveness and enables its economical and cost-effective use.



Völpker Spezialprodukte GmbH
Fabrikstraße 1 | 39393 Völpke | Germany
Tel. +49 (0) 39402 962-0
Fax +49 (0) 39402 215
application@voelpker.com
www.voelpker.com

Design: www.artfaktor.de



This flyer is printed on
certified recycled paper.

ecovadis



1st Edition | 03/2025

Disclaimer

The information contained herein are believed to be accurate and reliable as of the date issued. However, we do not warrant or guarantee the accuracy or reliability, in particular not for any specific intended use by the customer. It is the responsibility of those to whom we supply our products directly or indirectly to ensure that their use of the product complies with existing regulations, laws, legislations and proprietary rights. The information given by Völpker Spezialprodukte does not exempt the customer from carrying out inspections and analyses on goods purchased.