

PRODUCT INFORMATION

CEVO-process C-3310

Product Description

CEVO-process C-3310 is a well-balanced lubricant combination.

General Advantages

The mixture was engineered especially for the application in PVC for injection molding and extrusion process.

Examples of Use

The use of the one-pack permits the optimisation of plastification time, improves the flow behaviour of melt, causes a high melt stability and leads to a better demolding of parts. Furthermore the mixture reduces the influence of friction and works, in addition, as a chloride scavenger. We recommend to add amounts of 1.0 – 1.5 phr.

Delivery Specifications *

Characteristics	Unit	Target value	Method
Melting point *	°C	> 140	ASTM 3954
Colour	–	white	AA 3.2.1.505
Density	g/cm ³	1.00 – 1.02	Ph. Eur. 2.2.5

Packaging and Handling

Physical form	Powder
Packaging	Paper bag
Storage	Store at ambient temperature on a dry place. Protect from heat/overheating and direct sunlight. The minimum remaining period is 1.5 years and is defined as the minimum shelf life at the customer. Thereafter, tests of the chemical characteristics are recommended. The maximum shelf life of 5 years is indicated.

Safety

CEVO-process C-3310 is not classified as carcinogenic, mutagenic or reprotoxic; no health or environmental hazards are known, provided it is applied in industrial and professional settings.

Delivery Time and Availability

Standard delivery time: 2 – 3 weeks. Preconditions can be met for achieving shorter delivery times on standard products when demanded by the market.

Legislation

Product for technical applications.

- RoHS and CONEG compliant
- Ingredients listed in all relevant national inventories

For further information, please contact application@voelpker.com.